



Z-Finder Installation Instructions

1. Remove Z-Finder from packaging. The rubber eyecup should be attached. The mounting frame is installed on the open end of the Z-Finder.



2. Pull off the mounting frame from the Z-Finder and place the camera face down on either the capped camera body or capped lens so the LCD faces straight up.



3. If possible, take camera into subdued light. Turn camera on and hit MENU button. This should light up the picture area for placement of the mounting frame. If necessary, turn up the LCD brightness to see the picture area better.



4. Take the mounting frame and peel off the adhesive protection, then with two hands (fingers on the four corners of the frame), slowly bring the frame down to the LCD screen being careful to align the edges of the frame to the edges of the light LCD image. Slowly continue down until there is contact. Before applying pressure make sure that the frame is aligned and square.



5. Apply pressure with some weight such as a book for 24 hours too fully cure. After 24 hours, the Z-Finder will snap on and off the frame.



6. Z-Finder focus is achieved by dialing the red focus ring. The rubber eyecup can be oriented by simply rotating it.

7. If purchased, the lanyard loop screws into the 1/4 20" hole on either side of the Z-finder. The lanyard hook attaches to the loop.

8. If you are using the Z-Finder in cold or humid environments and experience fogging, purchase Clarity Fog Eliminator and rub cloth on both sides of the Z-Finder lens for 10-15 seconds.



9. To remove the mounting frame, if needed, just pinch the top and bottom sides of the frame so that the seal brakes. Then with a fingernail pull up one corner.

Questions? Please call **1.888.294.FILM**
or see www.Zacuto.com for video tutorial